

Repairing Big Mac Slabs Furniture Elastocured Product



CRACKS OR MAINTENANCE COAT:

Fill Crack with Big Mac Slabs Filler

Wipe with a damp cloth so filler is only in the crack.

When dry, light sand and wipe with damp cloth

Overcoat with Light Oak Elastocure

SCRATCHES / DAMAGE

Light sand to take off sharp edges

If back to bare wood – Apply Big Mac Slabs Light Oak Elastocure that is diluted 10% with water. Leave for 2 hours

If it is a deep scratch – apply filler & leave for 24 hours

Touch up the damaged area only with MID OAK Elastocure

Leave 2 hours and then overcoat the area with LIGHT OAK Elastocure

ROT / FLAKEY AREA'S / BLACK SPORES SPOT REPAIRS

Scrape all loose or soft material and then light sand to smooth off

Apply an Antifungal such as Wet & Forget to area & leave 3 hours

(or mix 20%Bleach/80% Water)

Apply Big Mac Slabs Light Oak that is watered down 10% and leave 2 hours

Apply Big Mac Slabs MID OAK Elastocure to the effected area

Leave 2 hours and overcoat with Big Mac Slabs LIGHT OAK Elastocure

A second coat of Light Oak Elastocure may be required to colour match.



MAKE THE MOST OF YOUR OUTDOORS

Free Phone 0508 BIG MAC (244 622)
Paraparaumu Creative Centre / 289 Mazengarb Road
fb.me@BigMacSlabs / admin@bigmacslabs.co.nz
www.bigmacslabs.co.nz